

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl. No. : 10/553,588
Applicant : Shigeki Imafuku et al
Filed : October 17, 2005
Patent No. : 7,337,533
Issue Date : March 4, 2008
Title : DEVICE AND METHOD FOR MOUNTING PART

Conf. No. : 1501
TC/A.U. : 3729
Examiner : Carl J. Arbes

Customer No. : 52054
Docket No. : NGB - 38837

CERTIFICATE OF CORRECTION TRANSMITTAL LETTER

Mail Stop Certificate of Correction Branch
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:


A Certificate of Correction under 35 U.S.C. 254 is hereby requested to correct Patent Office printing errors in the above-identified patent. Enclosed herewith is a proposed Certificate of Correction (Form No. PTO-1050) for consideration. Also enclosed is documentation in support of this request.

It is requested that the Certificate of Correction be completed and mailed at an early date to the undersigned attorney of record. The proposed corrections are obvious ones and do not in any way change the sense of the application.

We understand that a payment is not required since the errors were on the part of the Patent and Trademark Office in printing the patent.

Respectfully submitted,

PEARNE & GORDON LLP



Jeffrey J. Sopko, Reg. No. 27676

1801 East 9th Street, Suite 1200
Cleveland, OH 44114
(216) 579-1700

Date: July 11, 2008

**UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION**

Page 1 of 1

PATENT NO. : 7,337,533
APPLICATION NO.: 10/553,588
ISSUE DATE : March 4, 2008
INVENTOR(S) : Shigeki Imafuku et al

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In column 2, line 36, please delete "<". The line should read --- 11-330786/(1999) ---

In column 9, line 2, please delete "claim 2, 3, 4 or 5 can be satisfied." and insert therefor --- the claims can be satisfied. ---

In column 9, line 41, please delete "and a (a designates a margin to be added for avoiding" and insert therefor --- and α (α designates a margin to be added for avoiding ---

MAILING ADDRESS OF SENDER (Please do not use customer number below): PEARNE & GORDON LLP
1801 East 9th Street
Suite 1200
Cleveland, OH 44114

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1.0 hour to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Attention Certificate of Corrections Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

for moving the nozzle at the time of mounting the component so that it is possible to improve the production efficiency.

Please replace the paragraph on page 8, lines 4-9, with the following amended paragraph.

According to ~~Claims 1, 2 and 8~~the claims, it is possible to move down the nozzle in accordance with the height and position of each obstacle while overlapping with the obstacle when the nozzle is to be moved from the component supply portion to the board. Accordingly, when the nozzle has arrived at the mounting point above the board, the height of the nozzle can be set at a required minimum value so that the elevating stroke of the nozzle at the time of mounting the component becomes shortest.

Please replace the paragraph on page 12, lines 10-14, with the following amended paragraph.

The obstacle list may be registered into the computer by a person, or may be registered based on automatic measurement of the board camera etc. When only the conveyance rail, the nozzle station, the component camera or the referenced mark is registered in this obstacle list, requirements of [REDACTED]

disposed respectively in required positions and at required heights, but not allowed to be moved easily in order to ensure accuracy. Accordingly, a height high enough not to interfere with each of these obstacles (the component camera, the nozzle station, the reference mark, and the conveyance rail) has to be ensured as the height with which the nozzle 55 moves.

(Patent Document 1) Japanese Patent Publication JP-A-9-214182/(1997)

(Patent Document 2) Japanese Patent Publication JP-A- 2002-111284

(Patent Document 3) Japanese Patent Publication JP-A-

10 <Disclosure of the Invention>

In the aforementioned configuration, the nozzle 55 is moved while a height high enough not to interfere with each of the obstacles (the component camera, the nozzle station, the reference mark, the conveyance rail, etc.) is ensured as the height with which the nozzle moves. Even after the nozzle 55 has reached above the board, the nozzle 55 still moves at the same height. For this reason, when the nozzle 55 having arrived above a component mounting position on the circuit board is to mount the component, an elevating stroke of the nozzle 55 is so large that the production efficiency is lowered.

As shown in Fig. 13, a moving trajectory of the nozzle 55 at the time of mounting a component is as follows. The nozzle 55 is moved horizontally at a fixed height with a component height being set at H_a ((1) in Fig. 13). As soon as the nozzle 55 has reached just above a component mounting position P_0 , the nozzle 55 is stopped from moving horizontally and is moved down vertically by a height ΔH ((2) in Fig. 13) so as to mount the electronic component on the board 58. After that, the nozzle 55 is moved up vertically ((3) in Fig. 13). As soon as the nozzle 55 has reached a predetermined height, the nozzle 55 is stopped from moving up but is made to start to move horizontally ((4) in Fig. 13). To this end, times are required respectively for the horizontal movement operation and the elevating operation of the nozzle 55. Therefore, the operation time becomes so long that the production efficiency is lowered.

The present invention is to solve the foregoing problems. An object of the present invention is to provide a component mounting apparatus and a component mounting method in which time to move a nozzle can be shortened so that production efficiency can be improved.

effective.

In Step 6, the obstacle list shown in Fig. 3(a) by way of example is searched to find a highest one of the obstacles located between the current position of the nozzle and the position of the circuit board. In the case of Fig. 3(a), the nozzle station with the identification code B is the highest. Incidentally, in this search, obstacles out of a movement path of the nozzle may be excluded from the search. In order to simplify the processing, all the obstacles may be intended for the search. In Step 7, the nozzle is moved up to a height equal to a sum of a height (the largest height of the obstacle)

In Step 8, horizontal movement of the nozzle toward the circuit board is started. In Step 9, it is determined whether the nozzle has finished passing over the obstacle A or not while X- and Y-coordinate positions of the nozzle are monitored. When it is concluded that the nozzle has finished passing over the obstacle A, the routine of processing advances to a next step. The X and Y coordinates of the nozzle can be obtained as follows. For example, when the motors are servo motors, the X and Y coordinates of the nozzle can be read from encoders attached to the motors. When the motors are pulse motors, the X and Y coordinates of the nozzle can be obtained by counting pulses given to the motors. In Step 10, the current height of the nozzle is compared with a sum of the height of an obstacle (largest height of the obstacles B to D) the nozzle will pass over, and α . Here, only when the nozzle is higher, the routine of processing goes to Step 11, in which the nozzle is moved down to the height equal to the sum of (the largest height of the obstacles B to D) and α .

Incidentally, when the obstacle A is out of the movement path of the nozzle, Steps 9 to 11 does not have to be executed. For the sake of simplification of the processing, Steps 9 to 11 may be executed whether the obstacle A is out of the movement path of the nozzle or not. In Step 12, it is determined whether the nozzle has finished passing over the obstacle B or not while the X- and Y-coordinate positions of the nozzle are monitored. When it is concluded that the nozzle has finished passing over the obstacle B, the routine of processing advances to a next step.

In Step 13, the current height of the nozzle is compared with a sum of the height of an obstacle the nozzle will pass over (largest height of the obstacles C to D), and α . Here, only when the nozzle is higher, the routine of processing goes to Step 14, in which